


* For mounting on concrete + metallic plate, please contact us.

CLIPS	C max	Tightening torque (Nm)			Est'd weight
		Bolt or screw grade			
	mm	4.6	5.6	8.8	kg
41/125/BN	35	250	300	660	0,600
41/125/CN	40				0,640
41/125/DN	46				0,680
Admissible side load (kN)		50	60	125	

N : nose height, not compressed, adapted to the rail type (see table overleaf).

SUB-PARTS




All parts are hot dip galvanized.

Full designation	
41/125/BN or 41/125/CN or 41/125/DN	
Components	
①	1x 41/125/R
②	1x 41/125/35/N or 41/125/40/N or 41/125/46/N

For further anti-corrosion coating : see leaflet "Patented bolttable clips".

41/125

CLIP SELECTION FOR EACH RAIL							
	F mm	K mm	H mm	Weight kg/m	Mounting		
					with	without	
					pad		
A 65	175.0	65.0	75.0	43.10	41/125/BJ	-	
A 75	200.0	75.0	85.0	56.20	41/125/BJ	-	
A 100	200.0	100.0	95.0	74.30	41/125/BI	-	
A 120	220.0	120.0	105.0	100.00	41/125/CJ	41/125/BM	
A 150	220.0	150.0	150.0	150.30	41/125/CI	41/125/BJ	
MRS 51 (104 CR)	127.0	63.5	127.0	51.59	41/125/CM	41/125/BM	
MRS 52 (105 CR)	131.8	65.1	131.8	52.09	41/125/BI	-	
MRS 67 (135 CR)	131.8	76.2	146.0	66.97	41/125/CM	41/125/BM	
MRS 85 (171 CR)	152.4	101.6	152.4	84.83	41/125/CI	41/125/BJ	
MRS 87 A (PRI 85 R)	152.4	101.6	152.4	86.80	41/125/CH	41/125/BJ	
MRS 87 B (175 CR)	152.4	102.4	152.4	86.80	41/125/CJ	41/125/BM	
MR 151 (PR 7)	220.0	150.0	150.0	151.30	41/125/CI	41/125/BJ	
Vign 36	115.0	58.2	128.0	36.54	41/125/BJ	-	
Vign 46 (U 33)	134.0	62.0	145.0	46.36	41/125/BJ	-	
Vign 50 (U 50)	140.0	65.0	153.0	50.88	41/125/BI	-	
Vign 52	150.0	65.0	150.0	52.34	41/125/BJ	-	
Vign 55	134.0	62.0	155.0	56.07	41/125/CJ	41/125/BM	
S 41/10	125.0	67.0	138.0	41.38	41/125/BJ	-	
S 49	125.0	67.0	149.0	49.43	41/125/BI	-	
S 54	125.0	67.0	154.0	54.54	41/125/CM	41/125/BM	
S 64	150.0	74.0	172.0	64.92	41/125/CM	41/125/BM	
EB 50 T	140.0	72.0	151.0	50.10	41/125/BI	-	
UIC 54	140.0	70.0	159.0	54.43	41/125/BI	-	
UIC 60	150.0	72.0	172.0	60.34	41/125/BI	-	
56 CR	171.0	76.0	101.5	56.81	41/125/BI	-	
89 CR	178.0	102.0	114.0	89.81	41/125/CI	41/125/BJ	
101 CR	165.0	100.0	155.0	100.38	41/125/CH	41/125/BI	
BS 113 A	139.7	69.9	158.8	56.40	41/125/BI	-	
JIS 50 N	127.0	65.0	153.0	50.40	41/125/BI	-	
JIS 60	145.0	65.0	174.0	60.80	41/125/CM	41/125/BM	
CR 73	140.0	100.0	135.0	73.30	41/125/CJ	41/125/BJ	
CR 100	155.0	120.0	150.0	100.20	41/125/CH	41/125/BI	
AS 73 (MRS 73)	146.0	70.0	157.0	73.63	41/125/DM	41/125/BI	
AS 86 (MRS 86)	165.0	102.0	102.0	85.60	41/125/CI	41/125/BJ	

For rail sections other than those listed on this page, please contact us.

We reserve the right to discontinue or change specifications or design at any time without prior notice and without incurring any obligation whatsoever.

Darusín Kft.

Hungary, 2400 Dunaújváros, Neumann J. u. 16 • Tel: +36 25 503 930 • Fax: +36 25 503 931
E-mail: darusin@darusin.hu • webpage: www.darusin.hu