


* For mounting on concrete + metallic plate, please contact us.

CLIPS	B	C max	D	Tightening torque (Nm)			Est'd weight kg
				4.6	5.6	8.8	
	mm			4.6	5.6	8.8	kg
71/075/AN	23	33	36	150	200	400	0,670
71/075/BN	28	38	41				0,780
71/075/CN	32	42	45				0,890
71/075/DN	35	45	48				0,980
71/075/EN	41	51	54				1,100
Admissible side load (kN)				30	40	75	

N : nose height, not compressed, adapted to the rail type (see table overleaf).

SUB-PARTS




Full designation	Components
71/075/AN or 71/075/BN or 71/075/CN or 71/075/DN or 71/075/EN	① 1x 71/075/24/N
	② 1x 71/075/15 or 71/075/21 or 71/075/25 or 71/075/29 or 71/075/34

Anti-corrosion coating : see leaflet "Patented bolttable clips".

71/075

CLIP SELECTION FOR EACH RAIL

	F mm	K mm	H mm	Weight kg/m	Mounting	
					with	without
					pad	
A 55	150.0	55.0	65.0	31.80	71/075/BJ	71/075/AJ
A 65	175.0	65.0	75.0	43.10	71/075/BJ	71/075/AJ
A 75	200.0	75.0	85.0	56.20	71/075/BJ	71/075/AJ
A 100	200.0	100.0	95.0	74.30	71/075/CM	71/075/AJ
A 120	220.0	120.0	105.0	100.00	71/075/CI	71/075/BM
A 150	220.0	150.0	150.0	150.30	71/075/DJ	71/075/CM
MRS 51 (104 CR)	127.0	63.5	127.0	51.59	71/075/CI	71/075/BM
MRS 52 (105 CR)	131.8	65.1	131.8	52.09	71/075/CJ	-
MRS 67 (135 CR)	131.8	76.2	146.0	66.97	71/075/CJ	71/075/BM
MRS 85 (171 CR)	152.4	101.6	152.4	84.83	71/075/DM	71/075/BJ
MRS 87 A (PRI 85 R)	152.4	101.6	152.4	86.80	71/075/DM	71/075/BJ
MRS 87 B (175 CR)	152.4	102.4	152.4	86.80	71/075/DM	71/075/BM
MRS 125	180.0	120.0	180.0	125.00	71/075/EI	71/075/DM
MR 151 (PR 7)	220.0	150.0	150.0	151.30	71/075/DJ	71/075/CM
Vign 36	115.0	58.2	128.0	36.54	71/075/BI	71/075/AJ
Vign 46 (U 33)	134.0	62.0	145.0	46.36	71/075/BI	71/075/AJ
Vign 50 (U 50)	140.0	65.0	153.0	50.88	71/075/BI	71/075/AJ
Vign 52	150.0	65.0	150.0	52.34	71/075/BI	71/075/AJ
Vign 55	134.0	62.0	155.0	56.07	71/075/DM	71/075/BM
S 41/10	125.0	67.0	138.0	41.38	71/075/BJ	71/075/AJ
S 49	125.0	67.0	149.0	49.43	71/075/CJ	-
S 54	125.0	67.0	154.0	54.54	71/075/CJ	71/075/BM
S 64	150.0	74.0	172.0	64.92	71/075/CJ	71/075/BM
GX 40	127.0	63.5	127.0	39.80	71/075/CM	71/075/AJ
GX 42	131.8	65.1	131.8	42.16	71/075/BJ	71/075/AJ
EB 50 T	140.0	72.0	151.0	50.10	71/075/CM	71/075/AI
UIC 54	140.0	70.0	159.0	54.43	71/075/CM	-
UIC 60	150.0	72.0	172.0	60.34	71/075/CM	71/075/AJ
56 CR	171.0	76.0	101.5	56.81	71/075/CM	71/075/AI
89 CR	178.0	102.0	114.0	89.81	71/075/DM	71/075/CM
101 CR	165.0	100.0	155.0	100.38	71/075/DJ	71/075/CM
BS 113 A	139.7	69.9	158.8	56.40	71/075/CM	71/075/AI
JIS 37	122.2	62.7	122.2	37.20	71/075/BJ	71/075/AJ
JIS 40 N	122.0	64.0	140.0	40.90	71/075/CM	71/075/AJ
JIS 50 N	127.0	65.0	153.0	50.40	71/075/CJ	71/075/BM
JIS 60	145.0	65.0	174.0	60.80	71/075/DM	71/075/BM
CR 73	140.0	100.0	135.0	73.30	71/075/DM	71/075/BJ
CR 100	155.0	120.0	150.0	100.20	71/075/EM	71/075/CJ
AS 41	127.0	63.5	137.0	40.72	71/075/CM	71/075/AJ
AS 50	127.0	69.9	154.0	50.80	71/075/CJ	71/075/BM
AS 60	146.0	69.9	170.0	60.99	71/075/CJ	71/075/BM
AS 73 (MRS 73)	146.0	70.0	157.0	73.63	71/075/DJ	71/075/CM
AS 86 (MRS 86)	165.0	102.0	102.0	85.60	71/075/DM	71/075/BJ

For rail sections other than those listed on this page, please contact us.

We reserve the right to discontinue or change specifications or design at any time without prior notice and without incurring any obligation whatsoever.

Darusin Kft.

Hungary, 2400 Dunaújváros, Neumann J. u. 16 • Tel: +36 25 503 930 • Fax: +36 25 503 931
E-mail: darusin@darusin.hu • webpage: www.darusin.hu