


**GANTREX® MK0** pads have been specially designed for the soft mounting of crane rails, being mounted either continuously on steel, or a mixed support of steel and concrete, along with GANTREX® fixing clips type 21/020 and 51/015.

#### **GANTREX® MK0 pads :**

- are manufactured as a synthetic elastomer strip.
- reduce the wear of the rail and its support :
  - absorb the uneven surfaces;
  - improve the contact between rail and support.
- are specially resistant to wear, shear, crushing, oxygen and ultra-violet rays.

#### **Material characteristics :**

- Composition : elastomer type NR/SBR.
- Shore hardness : 70°A (DIN 53505).
- Tensile strength : 7 N/mm<sup>2</sup> (DIN 53455).
- Elongation : 200 %, break value (DIN 53455).
- Service temperature : from -15°C up to +70°C. For other temperatures, please consult us.



PAD

 **GANTREX<sup>®</sup>**

**MK0**

### **Dimensions :**

The **GANTREX<sup>®</sup> MK0** pads are supplied with a thickness of 4 mm.

The width is adapted according to the rail foot, taking into account the manufacturing tolerances.

The **GANTREX<sup>®</sup> MK0** pads are supplied in standard lengths of 10 m. Smaller lengths (minimum 4 m) can be supplied : please consult us.

For particular applications (namely circular tracks), very small lengths can be supplied, designed according to the track characteristics : please consult us.

### **Installation :**

For applications where the coefficient of friction is uncertain (e.g. presence of oil and/or water), it is recommended to install holding plates between the clips so as to ensure the pad remains in position.

---

*We reserve the right to discontinue or change specifications or design at any time without prior notice and without incurring any obligation whatsoever.*

### **DaruSín Kft.**

Hungary, 2400 Dunaújváros, Neumann J. u. 16 • Tel: +36 25 503 930 • Fax: +36 25 503 931  
E-mail: [darusin@darusin.hu](mailto:darusin@darusin.hu) • webpage: [www.darusin.hu](http://www.darusin.hu)